

VIP™ Signal Distributor



VIP™ Signal Distributor (required for systems over 24 panels) splits and amplifies the signal from the VIP™ Driver to the panels and is capable of 4-way, dual-channel splitting or 8-way, single-channel splitting.

FEATURES

- Distributes and amplifies the output from the VIP™ Drive for up to 192 panels (must not exceed LED quantity capacity)
- The VIP™ Signal Distributor is required for systems of 25 or more video panel arrays
- Serves as a 2-channel, 4-way or 1-channel, 8-way device (requires 2 VIP™ Drivers)
- You may link multiple units together for greater quantities
- Required for signal cable runs over 100 m (serves as a signal amplifier)

SPECIFICATIONS

- Control Protocol: LINSN
- Data Connectors: Neutrik® etherCON®
- Video Input: Neutrik® etherCON®(2)
- Video Output: Neutrik® etherCON®(8)
- Rackmount: 1U
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to IEC
- Power Input: IEC
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 40 W, 0.33 A @ 120 V, 60 Hz
- Power and Current: 40 W, 0.19 A @ 208 V, 60 Hz
- Power and Current: 40 W, 0.17 A @ 230 V, 50 Hz
- Weight: 5 lb (2.27 kg)
- Dimensions: 19 x 10 x 1.7 in (483 x 254 x 44 mm)
- Housing Material: Aluminum alloy
- Approvals: CE, FCC